

LTE10

STANDARD CONFIGURATION

Performance Parameters

Operating Weight	1000kg
Engine Model	KOOP192F
Rated Power	10.3Kw/14hp
Bucket Capacity	0.02m ³
Bucket Width	400mm
Max Digging Force	10.3Kn
System Working Pressure	18Mpa
Swing Speed	12rpm
Traveling Speed	2km/h
Gradeability	30°
Ground Pressure	22Kpa

Operating Range

Max. Digging Distance	2450mm
Max. Digging Depth	1320mm
Max. Digging Height	2500mm
Max. Dumping Height	1820mm
Min. Turning Radius	1190mm

Overall Dimensions

Overall Length	2200mm
Overall Width	940mm
Overall Height	2150mm
Min. Ground Clearance	380mm
Track Ground Length	1200mm
Track Width	180mm

※The parameters are subject to change without notice



OPTIONAL CONFIGURATION



STANDARD CONFIGURATION

Changchai 192F diesel engine / High-precision multitandem valve / High-quality motor / Nine-tooth spline / gear pump / Imported cylinder, tubing with build-in NOK sealing ring / Adjustable blade / Wear-resistant / engineering rubber track / Adjustable driver seat / Standard bucket / Steyr / Flameout cable

APPLICATION

Applicable to agroforestry planting, farmland leveling, garden cultivation, repairing pavement, basement and interior construction, farming, vegetable greenhouse and other working environment.

