

LTE17

STANDARD CONFIGURATION

Performance Parameters

Operating Weight	1700kg
Engine Model	LaidongLD385
Rated Power	29Kw/39hp
Bucket Capacity	0.04m ³
Bucket Width	400mm
Max Digging Force	14Kn
System Working Pressure	18Mpa
Swing Speed	12rpm
Traveling Speed	2.8km/h
Gradeability	35°
Ground Pressure	25Kpa

Operating Range

Max. Digging Distance	2500mm
Max. Digging Depth	1900mm
Max. Digging Height	2820mm
Max. Dumping Height	2000mm
Min. Turning Radius	1190mm

Overall Dimensions

Overall Length	2250mm
Overall Width	1100mm
Overall Height	2200mm
Min. Ground Clearance	380mm
Track Ground Length	1370mm
Track Width	180mm

※The parameters are subject to change without notice



OPTIONAL CONFIGURATION



STANDARD CONFIGURATION

Changchai 192F diesel engine / High-precision multitandem valve / High-quality motor / Nine-tooth spline / gear pump / Imported cylinder, tubing with build-in NOK sealing ring / Adjustable blade / Wear-resistant / engineering rubber track / Adjustable driver seat / Standard bucket / Steyr / Flameout cable

APPLICATION

Applicable to agroforestry planting, farmland leveling, garden cultivation, repairing pavement, basement and interior construction, farming, vegetable greenhouse and other working environment.

